

Material Safety Data Sheet

1. Identification of the material and supplier

Product name Synthetic Power Steering Fluid

Product code: 3150

Product use Automotive Power Steering Fluid.

Supplier Royal Precision Lubricants Pty Ltd

40 Kimberly Road,

Dandenong South, Victoria, 3175.

ABN 72 155 989 165

Telephone (03) 9768 2441

EMERGENCY TELEPHONE NUMBER (03) 9768 2441

2. Hazards identification

Statement of hazardous/dangerous nature NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS

While this material is not considered to be hazardous, it should be handled in accordance with good industrial hygiene and safety practices.

Safety Phrase

S2- Keep out of the reach of children.

3. Composition/information on ingredients

Synthesized hydrocarbons and other ingredients

This product does not contain any hazardous ingredients at or above regulated thresholds.

4 .First-aid measures

Skin contact

Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.

Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms appear.

Eve contact

In case of contact, immediately flush eyes with a copious amount of water for at least 15 minutes. Get medical attention if irritation occurs.

Ingestion

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects.

5. Fire-fighting measures

Extinguishing Media Suitable

In case of fire, use water fog, foam, dry chemical or carbon dioxide extinguisher or spray.

Do not use water jet.

Protection of fire-fighters

Fire-fighters should wear self-contained positive pressure breathing apparatus (SCBA) and full turnout gear.

Special fire-fighting procedures

None identified

Unusual fire/explosion Hazards

This material is not explosive as defined by established regulatory criteria.

Hazards from combustion products

Decomposition products may include the following materials:

carbon oxides sulfur oxides phosphorus oxides metal oxide/oxides

6. Accidental release measures

Emergency Procedures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and clean-up

If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilt material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information.

Large Spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1for emergency contact information and section 13 for waste disposal.

Small Spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Storage

Keep container tightly closed. Keep container in a cool, well-ventilated area. Store under cover away from heat and sources of ignition. Reference should be made to Australian Standard AS1940- The storage and handling of flammable and combustible liquids. Products should not be stored over 60°C.

Additional information-Storage

Classified as combustible liquid Class C2 (AS 1940).

Product contaminated rags paper or material used to absorb spillages represent a fire hazard and should not be allowed to accumulate. Dispose of safely immediately after use.

8. Exposure controls/personal protection

Ingredient name Occupational exposure limits

Base oil - unspecified NOHSC (Australia). TWA: 5 mg/m3 8 hour(s). Form: Oil mist, mineral.

Whilst specific OELs for certain components are included in this data sheet, it should be noted that other components of the

preparation will be present in any mist, vapour or dust produced. For this reason, the specific OELs may not be applicable to the product and are provided for guidance purposes.

Control Measures

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Biological Limit Values

No biological limit allocated.

Personal protective equipment

Hands

Wear protective gloves if prolonged or repeated contact is likely. Chemical resistant gloves. Recommended: Nitrile gloves.

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eves

Safety glasses with side shields.

Skin and Body

Avoid prolonged or repeated contact with skin. Wear protective clothing if prolonged or repeated contact is likely.

Respiratory system

Avoid breathing of vapours, mists or spray. Select and use respirators in accordance with AS/NZS 1715/1716. When mists or vapours exceed the exposure standards then the use of the following is recommended: Approved respirator with organic vapour and dust/mist (TypeP1) filters. Filter capacity and respirator type depends on exposure level

9. Physical and chemical properties

Flash point > 205 °C
Colour Red
Physical state Liquid
Density 0.8380 kg/L
Solubility Insoluble in water
pH Not applicable
Viscosity 7.2 cst @ 100°C

10 . Stability and reactivity

Hazardous polymerization

Will not occur

Stability

This product is stable

Conditions to Avoid

Keep away from fire, extreme heat, and oxidizing compounds

Incompatibility with various substances/Hazardous Reactions

Reactive with oxidizing compounds

Hazardous Decomposition Products

Product does not decompose at ambient temperatures.

11. Toxicological information

Effects and symptoms

Eyes

Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.

Skin

Prolonged or repeated contact can de-fat the skin and lead to irritation and/or dermatitis.

Inhalation

Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.

Ingestion

Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhea.

Carcinogenic effects

No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen by ACGIH, the International Agency for Research on Cancer (IARC), the European Commission (EC), or the National Occupational Health and Safety Commission (Australia).

12 .Ecological information

Ecotoxicity

Not classified as environmentally hazardous in accordance with the 'Approved Criteria for Classifying Hazardous Substances' [NOHSC (1008)/2004 as amended and adapted].

Biodegradability

The biodegradability of this material has not been determined.

Mobility

Spillages may penetrate the soil causing ground water contamination.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

13. Disposal considerations

Disposal Consideration / Waste information

Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and national regulations.

Special Precautions for Landfill or Incineration

No additional special precautions identified.

14 .Transport information

Not classified as dangerous for transport (ADG, IMDG, ICAO/IATA).

Special precautions for user

No known special precautions required. See Section: "Handling and storage" for additional information.

15. Regulatory information

Standard for the Uniform Scheduling of Drugs and Poisons Not regulated.

Control of Scheduled Carcinogenic Substances Ingredient name Schedule No Listed Substance Inventories

Other regulations

16. Other information

Prepared by Royal Precision Lubricants Pty Ltd

Notice to reader

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses, but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. For further information, please contact Royal Precision Lubricants.

Key to abbreviations

AMP = Acceptable Maximum Peak

ACGIH = American Conference of Governmental Industrial Hygienists, an agency that promulgates exposure standards.

ADG = Australian Code for the Transport of Dangerous Goods by Road and Rail

ADG Code = Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Number = Chemical Abstracts Service Registry Number

HAZCHEM Code = Emergency action code of numbers and letters which gives information to emergency services. Its use is required by the ADG Code for Dangerous Goods in bulk.

ICAO = International Civil Aviation Organization.

IATA = International Air Transport Association, the organization promulgating rules governing shipment of goods by air.

IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.

IP 346 = A chemical screening assay for dermal toxicity. The European Commission has recommended that Method IP 346 be used as the basis for labelling certain lubricant oil base stocks for carcinogenicity. The EU Commission has stipulated that the classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. (See Note L, European Commission Directive 67/548/EEC as amended and adapted.) DMSO is a solvent. NOHSC = National Occupational Health & Safety Commission, Australia

TWA = Time weighted average

STEL = Short term exposure limit

UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.