



Product Data Sheet

M3 Supreme

Quality Motor Oil for Superior Protection

M3 SUPREME is a high performance engine oil that meets the requirements of modern engine manufacturers.

Summary of Benefits:

- Has superior sludge and varnish control for cleaner engines.
- Very good low temperature viscometrics for reduced wear at start up.
- Engine oils described as service category SJ were first introduced in 1996 for use in current and earlier passenger cars, utilities, vans, and light truck operations under manufacturers recommended oil drain intervals.
- Suitable for use in LPG and lightly loaded diesel engines both naturally aspirated and turbocharged.

Specifications:

- API: SJ/CF
- SAE Viscosity: 20W-50
- ACEA: A2-96 Issue 2, A3-98, B2-98, B3-98, E2-96 Issue 2
- VW: 500.00, 501.00
- Ford: ESE-M2C 153-E
- MIL-L-46152E, MIL-L-2104 E

Product Code: 1001

Product Size: 20L, 205L

14.02.19

WWW.ROYALLUBRICANTS.COM.AU Brisbane: 1-7 Potassium Street, Narangba, QUEENSLAND, AUSTRALIA 4504 Tel: +61 7 3203 0089 Fax:+61 7 3203 3700 ...DRIVEN BY PERFECTION Melbourne: 40 Kimberley Road, Dandenong South, VICTORIA, AUSTRALIA 3175 Tel: +61 3 9768 2441 Fax:+61 3 9768 3325





Product Data Sheet

M3 Supreme

Typical Characteristics:

Density at 15°C (kg/L)	0.896
Flash Point COC (°C)	225
Pour Point (°C)	-21
Kinematic Viscosity at 40°C mm2/s (cSt)	160
Kinematic Viscosity at 100°C mm2/s (cSt)	19.0
Viscosity Index	135

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website <u>www.royallubricants.com.au</u> or by email <u>info@royallubricants.com.au</u>

14.02.19

WWW.ROYALLUBRICANTS.COM.AU Brisbane: 1-7 Potassium Street, Narangba, QUEENSLAND, AUSTRALIA 4504 Tel: +61 7 3203 0089 Fax:+61 7 3203 3700 ...DRIVEN BY PERFECTION Melbourne: 40 Kimberley Road, Dandenong South, VICTORIA, AUSTRALIA 3175 Tel: +61 3 9768 2441 Fax:+61 3 9768 3325