

## Product Data Sheet

### **Senso Heavy 25W-60**

*Quality Motor Oil Suitable For Older Engines*

**Senso Heavy** is a heavy-duty passenger car lubricant recommended for protection of engines especially where low oil pressure or high consumption is involved. Also suitable for noisy or worn engines that burn oil or blow smoke, in high ambient operating temperatures and high loading associated with caravan or trailer towing.

#### **Summary of Benefits:**

- Ideal where low oil pressure or high consumption is involved.
- Suitable where high loading associated with caravan or trailer towing
- Performs well in noisy or worn engines.
- Ideal in engines that burn oil or blow smoke.
- Holds better viscosity in higher operating temperatures.
- Ideal in older diesel and LPG engines.

#### **Specifications:**

- API: SJ/CF
- SAE Viscosity: 25W-60

**Product Code:** 1601

**Product Size:** 5L, 20L, 205L



14.02.19 V1

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089 Fax: +61 7 3203 3700**

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441 Fax: +61 3 9768 3325**

## **Senso Heavy 25W-60**

## Product Data Sheet

### **Typical Characteristics:**

Density at 15°C (kg/L)	0.899
Flash Point COC (°C)	230
Pour Point (°C)	-25
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	260
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	25.0
Viscosity Index	123
Sulphated Ash (%m)	<1.0
Colour	Clear and bright

*\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

### **Storage:**

*All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.*

### **Health, Safety and Environment:**

*A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.*

The Safety Data Sheet is available at Royal Precision Lubricants website [www.royallubricants.com.au](http://www.royallubricants.com.au) or by email [info@royallubricants.com.au](mailto:info@royallubricants.com.au)

14.02.19 V1

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089** Fax: +61 7 3203 3700

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441** Fax: +61 3 9768 3325