

**SMALL ENGINE**

## **Four Stroke**

*Premium, Lawn Mower and Stationary Engine Motor Oil*

## Product Data Sheet

**Four Stroke** Lawn Mower and Stationary Engine Oil is a monograde SAE Viscosity 30 crankcase oil designed for small petrol and diesel engines. It controls oil consumption and deposits and protects against rust, corrosion and wear, leading to longer engine life. Recommended for four stroke petrol lawn mower engines running on leaded, unleaded or lead replacement petrol. Especially suitable for Briggs and Stratton engines and for small four stroke petrol and diesel stationary engines. It is not recommended for two stroke petrol or two stroke diesel engines.

### **Summary of Benefits:**

- Meet warranty service requirements for a wide range of modern diesel and petrol engines.
- Maximise engine life by controlling deposits and protecting against wear of highly loaded components under severe service conditions.
- Reduce maintenance costs by maximising oil filter life and engine overhaul periods.
- Maintain excellent control of oil consumption.
- Protect against rust and corrosion.

### **Specifications:**

- API: SG/CD
- SAE Viscosity: 30
- ACEA: E2
- General Motors: 6094M
- Ford: M2C 121-E3
- US Military: MIL-L-2104 F, MIL-L-46152 D
- Briggs & Stratton Service: SE/SF/SG SAE 30
- Japan: Japanese CD

**Product Code:** 1830

**Product Size:** 1L, 2.5L, 5L, 20L, 205L



14.02.19 V1

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089 Fax: +61 7 3203 3700**

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441 Fax: +61 3 9768 3325**

**SMALL ENGINE**

**Four Stroke 30**

*Premium, Lawn Mower and Stationary Engine Motor Oil*

## Product Data Sheet

**Typical Characteristics:**

Density at 15°C (kg/L)	0.894
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	102
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	11.5
Viscosity Index	99
Sulphated Ash (%m)	0.94
Base Number (mg KOH/G)	6.4

*\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

**Storage:**

*All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.*

**Health, Safety and Environment:**

*A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.*

The Safety Data Sheet is available at Royal Precision Lubricants website [www.royallubricants.com.au](http://www.royallubricants.com.au) or by email [info@royallubricants.com.au](mailto:info@royallubricants.com.au)

14.02.19 V1

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089 Fax: +61 7 3203 3700**

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441 Fax: +61 3 9768 3325**