

Product Data Sheet

HPDD 40

High Performance Engine Oil for Superior Wear and Protection

HPDD This is a low sulphated ash SAE diesel engine oil designed for use in Detroit Diesel 2 stroke engines – naturally aspirated or turbocharged.

It is also suitable for a large variety of 4-stroke diesel engines and can be used in 4-stroke petrol engines. Also suitable for a range of automotive transmissions requiring SAE 40 engine oils.

Summary of Benefits:

- Low ash formulation to minimise exhaust valve deposit formation.
- Provides excellent protection against corrosion and wear throughout the recommended oil drain period.
- Anti-wear and anti-oxidants have been optimised for diesel engines to provide longer oil life.
- The detergent/dispersants control soot thickening and keep pistons clean.
- **HPDD** is primarily for Detroit Diesel two stroke engines.

Specifications:

- API: CF/CF-2/SG
- SAE: 40
- Detroit Diesel: 7SE2709505
- ACEA: E1
- Mercedes Benz: MB 227.1
- MIL-L-46152B, MIL-L-2104 D

Product Code: 2200

Product Size: 20L, 205L, 1000L



14.02.19 V1

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325



**THE INNOVATIVE
AUSTRALIAN**

Product Data Sheet

HPDD 40

High Performance Engine Oil for Superior Wear and Protection

Typical Characteristics:

Density at 15°C (kg/L)	0.892
Flash Point COC (°C)	225
Pour Point (°C)	-15
Kinematic Viscosity at 40°C mm ² /s (cSt)	140
Kinematic Viscosity at 100°C mm ² /s (cSt)	14.8
Total Base Number (mgKOH/g)	7.6
Sulphated Ash (%m)	<1.0

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email info@royallubricants.com.au

14.02.19 V1

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325