



**THE INNOVATIVE
AUSTRALIAN**

MULTIFARM

Product Data Sheet

Multi-Purpose Farm Engine, Transmission and Hydraulic oil

MultiFarm is formulated as a Super Tractor Oil Universal for engines, transmissions, differentials, wet brake systems, power take off and hydraulic units. **MultiFarm** is the ideal oil to rationalise farm lubricants without loss of lubricant protection and equipment performance. Transmission & Gearboxes are completely protected due to the load carrying thermal stability of **MultiFarm**.

Summary of Benefits:

- A multifunctional oil of the highest quality for all agricultural and off road plant where an oil of this type is called for by major manufacturers.
- This high-performance oil is blended for excellent results in all tractor gear boxes, main transmissions and associated machinery, as well as superior performance in agricultural hydraulic systems.

Specifications:

- API: CE, CD, CF-4, CG-4/SE, SF, GL-4, GL-5 (low speed/high torque)
- SAE Viscosity: 15W-40
- ACEA: E3
- Allison: C-4
- Case-IH: MS 1207
- Caterpillar: TO-2
- Ford: M2C-159B/C
- John Deere: JDM J27
- Massey Ferguson: CMS 1139, 1144, 1145
- MAN: 271
- Mercedes Benz: MB 227.1, 228.1, 228.3
- MIL-L-2104 D
- New Holland: 82009201/2/3
- ZF: TE-ML 06A, 06B, 06C, 07B

Product Code: 2600

Product Size: 20L, 205L, 1000L

V1.2. 6.23

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325



**THE INNOVATIVE
AUSTRALIAN**

MULTIFARM

Multi-Purpose Farm Engine, Transmission and Hydraulic oil

Product Data Sheet

Typical Characteristics:

Density at 15°C (kg/L)	0.884
Flash Point COC (°C)	200
Pour Point ASTM (°C)	-30
Kinematic Viscosity at 40°C ASTM D445 mm ² /s (cSt)	105
Kinematic Viscosity at 100°C ASTM D445 mm ² /s (cSt)	14.8
Viscosity Index, ASTM D2270	146

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email info@royallubricants.com.au

V1.2. 6.23

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325



**THE INNOVATIVE
AUSTRALIAN**

Product Data Sheet

V1.2. 6.23

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325