



**THE INNOVATIVE
AUSTRALIAN**

Auto Trans M

Product Data Sheet

For use in Mitsubishi Automatic Transmissions

Auto Trans Fluid M has been specially developed to meet the friction co-efficient requirements of the damper clutch system in Mitsubishi Magna automatic transmissions, and is recommended for use in the KM175 and KM177 automatic transmissions fitted to Mitsubishi Magnas from January 1988.

Auto Trans Fluid M can be used as top up or fill for the automatic transmissions of the following Mitsubishi models: Colt, Cordia, Gallant, Lancer, Nimbus, Pajero, Starwagon and Triton. This product must not be used in Borg Warner transmissions or power steering.

Summary of Benefits:

- Meets the demanding Mitsubishi performance requirements.
- Very good gear durability from specialized additives.
- High stable fluid ideally suited to long distance towing in hot weather.
- Smooth gear changes due to higher static and dynamic co-efficient friction.
- Low noise and no vibration from the damper clutch.

Specifications:

- Mitsubishi: Magna, ES-X64022SP3
- Hyundai: Automatic Transmissions (suitable for most)

Product Code: 3300

Product Size: 5L, 20L, 205L, 1000L

14.02.19 V1

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325



**THE INNOVATIVE
AUSTRALIAN**

Product Data Sheet

Auto Trans M

For Use in Mitsubishi Automatic Transmissions

Typical Characteristics:

Specific Density at 15°C (kg/L)	0.848
Flash Point COC (°C)	224
Pour Point (°C)	-36
Kinematic Viscosity at 40°C mm ² /s (cSt)	40
Kinematic Viscosity at 100°C mm ² /s (cSt)	7.2
Viscosity Index	144

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email info@royallubricants.com.au

14.02.19 V1

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325