

Agritrans 10W-30

Superior Quality Universal Tractor Transmission Fluid

Product Data Sheet

Agritrans Universal Tractor Transmission Oil is a multi-purpose oil suited to tractors requiring a common oil for transmissions, hydraulics, differentials, final drives, wet clutches and brakes. The anti-squawk additive ensures effective operation of wet brakes. **Agritrans** has been specifically developed to meet a wide range of specifications from most modern tractor and hydraulic pump OEM's.

Summary of Benefits:

- Superior gear wear protection.
- Correct frictional characteristics ensure quiet wet brake operation.
- Proven field performance.
- Good anti-foam characteristics.
- Excellent shear stability and thermal/oxidation stability provide long fluid life.

Specifications:

- API: GL-4
- SAE Viscosity: 10W-30
- AGCO, Allis, Chalmers: Power Fluid 821XL
- Allison: C-4
- Case-IH: MS 1204,1205,1206,1207,1209,1210, B-6, B-7
- Case New Holland: MAT 3525 (FNHA-2-C-201), 3526
- Case New Holland: MAT 3505, 3540
- Caterpillar: TO-2
- Deutz, Allis: 246634, 257541, 272843
- Ford: M2C 77-A, M2C 86-B/C, M2C-134 A/B/C/D
- John Deere: JDM J14A,B, C, Hygard J20C/D, Quatrol
- KUBOTA: UDT, Super UDT
- Massey Ferguson: M1110, 1127,1129,1135,1138, M1141,
- Massey Ferguson: M1143,1145
- Volvo: VCE WB101, 1273.03
- White Farm (AGCO) Q-1705, 1722, 1766B, 1802, 1826
- ZF: TE-ML 03E, 05F, 06K, 17F, 21F



V1.3 6.23

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325

Product Data Sheet

Hydraulic Specifications:

- Sperry Vickers Eaton
- I-286-S(Industrial)
- M2950-S(Mobile)
- M2952-S(Mobile)
- 35VQ25
- Denison
- HF-0, HF-1, HF-2

Product Code: 4200

Product Size: 5L, 20L, 205L, 1000L

Typical Characteristics:

Density at 15°C (kg/L)	0.848
Flash Point COC (°C)	190
Pour Point (°C)	-35
Kinematic Viscosity at 40°C mm ² /s (cSt)	68
Kinematic Viscosity at 100°C mm ² /s (cSt)	9.2
Viscosity Index	135

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email: info@royallubricants.com.au

V1.3 6.23

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325