

Product Data Sheet

Nail & Staple Gun Oil

Premium Quality, Anti-Wear Lubricating Fluid

Nail and Staple Gun Oil is a premium quality mineral based oil formulated with anti-wear, anti-oxidation, anti-foam and anti-corrosion additives. Suitable for manual and automatic lubricating applications. Oil equipment daily to increase tool efficiency.

Summary of Benefits:

- These oils offer superior performance in oxidation protection, thermal stability, water tolerance and pump durability.
- Anti-foam, anti-oxidants & anti-wear additives have been optimised for use where machine performance is not affected by fluctuating temperatures.

Specifications:

Cincinnati Milacron: P-68, P-69, P-70

Denison: HF-1, HF-2, HF-0

DIN: 51524 Part 2

• Eaton: Brochure 694 for 35VQ25A (formerly M-2950-S and I-286-S)

Ford: M6 C32

GM: LS2

AFNOR: NF E48-603 HM

Product Code: 6004

Product Size: 500ML, 5L

15.3.19 v1

WWW.ROYALLUBRICANTS.COM.AU
Brisbane:

1-7 Potassium Street, Narangba, QUEENSLAND, AUSTRALIA 4504 **Tel: +61 7 3203 0089** Fax:+61 7 3203 3700 ...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South, VICTORIA, AUSTRALIA 3175 **Tel: +61 3 9768 2441** Fax:+61 3 9768 3325



Nail & Staple Gun Oil

Product Data Sheet

Typical Characteristics:

Density at 15°C (kg/L)	0.880
Kinematic Viscosity at 40°C mm2/s (cSt)	68
Kinematic Viscosity at 100°C mm2/s (cSt)	8.9
Viscosity Index	104
Flash Point COC (°C)	195
Pour Point (°C)	-30
Colour	Clear

^{*}Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au
or by email info@royallubricants.com.au

15.3.19 v1

1-7 Potassium Street, Narangba, QUEENSLAND, AUSTRALIA 4504 **Tel: +61 7 3203 0089** Fax:+61 7 3203 3700

...DRIVEN BY PERFECTION

40 Kimberley Road, Dandenong South, VICTORIA, AUSTRALIA 3175 **Tel:** +61 3 9768 2441 Fax:+61 3 9768 3325