

Brake & Clutch Fluid

High Performance, Dot 4 Brake Fluid

Product Data Sheet

Brake and Clutch Fluid is a moisture resistant, high performance brake fluid. It is designed for the braking systems of cars, trucks and buses and meets the latest Australian and international standards.

Brake and Clutch Fluid has high temperature resistance and low moisture absorption providing superior boiling point and high vapour lock temperature throughout its service life.

Summary of Benefits:

- High Boiling Point
- Moisture Resistant
- Minimises Corrosion

Specifications:

- SAE: J 1704
- ISO: 4925
- HN 1796
- Ford: ESW-FM6C-2, ESZ-M6C-55A
- GMH: HN 1796
- Australian Standard: AS 1960.1
- FMVSS 116

Product Code: 6010

Product Size: 500ml, 1L, 5L, 20L



15.3.19 v1

Product Data Sheet

Brake & Clutch Fluid

Typical Characteristics:

Density @ 15c, kg/L	1.074
Colour	blue
Equilibrium Boiling Point	243 - 265
Viscosity cSt @ -40 (°C)	1250
Viscosity cSt @100 (°C)	2.4
Wet ERBP (°C)	155

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email info@royallubricants.com.au

15.3.19 v1