

Long Life Air Compressor Oil

Premium Quality, Extended Life Air Compressor Oil

Long Life Air Compressor Oil is formulated from hydro cracked base stocks with special non-hydrolysing anti-wear additive. It is suitable for rotary screw, reciprocating and centrifugal compressors operating under severe conditions.

Summary of Benefits

- Minimum deposit forming.
- Protects compressor components from wear.
- Low wear as a result of excellent rust protection and high film strength.
- Separates readily from water.

Specifications:

- DIN51551 Part 1

Product Code: 7018

Product Size: 500ml, 5L

Typical Characteristics:

Density at 15°C (kg/L)	0.876
Flash Point COC (°C)	205
Pour Point (°C)	-18
Kinematic Viscosity at 40°C mm ² /s (cSt)	64
Kinematic Viscosity at 100°C mm ² /s (cSt)	8.5
Viscosity Index	103
C.C Residue (%)	0.01

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

V1.1 10/17

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



Long Life Air Compressor Oil

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.

V1.1 10/17

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia, 4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

