



**THE INNOVATIVE
AUSTRALIAN**

Product Data Sheet

Ingear Gear Oils Range

Premium, Heavy Duty Industrial Gear Oil Meeting Industrial Steel 224

Ingear IGO are a premium quality extreme pressure gear oil range for use in enclosed gear boxes in industrial applications and may also be used for plain bearings where high loadings or stresses are encountered.

Summary of Benefits:

- Contains anti-corrosion additives that prevent problems arising from the entry of water through air vents particularly in high humidity conditions.
- Anti-oxidant additives substantially control the effects of high thermal loading that is encountered in enclosed gearboxes.
- These gear oils demulsify quickly preventing the carry-over of water and the formation of emulsions, thus giving longer lubricant and gear component life.

Specifications:

- API GL-3
- US Steel 224
- AIST 224
- ISO 129 25-1
- AGMA: 9005-E02
- Flender Rev. 16
- DIN 51517 (Part 3)

Product Code: 7020-7025

Product Size: 20L, 205L, 1000L

V1.2 6.23

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325

Product Data Sheet

Ingear Oils

Typical Characteristics:

	ISO: 68	100	150	220	320	460
Density at 15°C (kg/L)	0.87	0.89	0.91	0.91	0.925	0.92
Kinematic Viscosity at 40°C	68	100	150	220	320	450
Kinematic Viscosity at 100°C	9.1	11.4	15	19	25	31
Viscosity Index	109	100	100	97	100	99
Flash Point COC (°C)	>220	>220	>220	>220	>240	>260
Pour Point (°C)	-20	-20	-15	-15	-15	-12
Colour	Clear	Clear	Clear	Clear	Clear	Clear

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email: info@royallubricants.com.au

V1.2 6.23

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325