

Pneumatic Air Tool

Product Data Sheet

High Grade Anti-Wear Performance

Pneumatic Air Tool Oil has been specially developed for use in all types of air and pneumatic equipment. It possesses superior anti-wear characteristics, as well as excellent control over water washing, corrosion and fog formation. Pneumatic Air Tool Oil provides effective lubrication in the presence of water, good low temperature lubrication and offers excellent resistance to oxidation and gumming. Pneumatic Air Tool Oil provides extended Air Tool life and reduced maintenance and repair costs.

Summary of Benefits:

- Excellent extreme pressure properties to protect tools from seizure.
- Good adherence to wet surfaces.
- Good rust prevention properties

Recommendations

Air Tool Oil is suitable for use in pneumatically operated percussion/ rotary air tools all year in heated industrial plants. For small high-speed air operated drills at low ambient temperatures.



Product Code: 7040

Product Size: 500ml, 5L, 20L

V1.1 07/19

WWW.ROYALLUBRICANTS.COM.AU Brisbane:

1-7 Potassium Street, Narangba, QUEENSLAND, AUSTRALIA 4504 **Tel: +61 7 3203 0089** Fax:+61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South, VICTORIA, AUSTRALIA 3175 **Tel: +61 3 9768 2441** Fax:+61 3 9768 3325



Product Data Sheet

Pneumatic Air Tool

Typical Characteristics:

Viscosity @ 40°C	32 cSt (Typical)
Viscosity @ 100°C	5.4 cSt (Typical)
Viscosity Index	102
Density @ 15°C	0.87 kg/L
Flash Point COC (°C)	>209
Pour Point (°C)	-29

^{*}Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au
or by email: info@royallubricants.com.au

V1.1 07/19

1-7 Potassium Street, Narangba, QUEENSLAND, AUSTRALIA 4504 **Tel: +61 7 3203 0089** Fax:+61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South, VICTORIA, AUSTRALIA 3175 **Tel: +61 3 9768 2441** Fax:+61 3 9768 3325