

Product Data Sheet

Vacuum Pump Oil 68

Premium Anti-Wear Formulation

Vacuum Pump Oil 68 is a highly refined mineral based products manufactured specifically for the lubrication of vacuum pumps used in the dairy industry and some laboratory applications.

Summary of Benefits

- Superior oxidation resistance.
- Excellent anti-wear properties <u>without</u> the use of zinc containing additives.
- Advanced formula eliminates the possibility of vapour pressure increase.
- Excellent demulsibility ensure it readily separates from water providing pump durability.

Specifications:

SAE 20, ISO Viscosity 68

Product Code: 7070

Product Size: 20L, 205L, 1000L



40 Kimberly Road, Dandenong South, Victoria Australia 3175 PO Box 4580, Dandenong South, Victoria Australia 3164 Telephone: 61+3 9768 2441 Fax: 61+3 9768 3325







Product Data Sheet

Vacuum Pump Oil 68

Typical Characteristics:

Density @ 15°C	0.884
Kinematic Viscosity @ 100°C, cSt	8.8
Kinematic Viscosity @ 40°C, cSt	68
Viscosity Index	100
Flash Point °C	210
Pour Point °C	-8
Aniline Point °C	105

^{*}Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.



40 Kimberly Road, Dandenong South, Victoria Australia 3175 PO Box 4580, Dandenong South, Victoria Australia 3164 Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325



