

Product Data Sheet

Lithplex EP2

High Temperature, Extreme Pressure Lithium Complex Grease

Lithplex Grease is an NLGI No. 2 multipurpose, extreme pressure, high melting point, lithium complex grease which contains a light tackiness agent. It offers significant advantages over conventional soap based and clay-based greases in terms of shear stability, thermal stability, water resistance and pump ability. It has a high drop point and may be used at temperatures as high as 150°C and up to 220°C intermittent with a 4-ball weld test of 620kg.

Summary of Benefits

- Excellent extreme pressure performance
- Stays in place to lubricate and seal effectively
- Good mechanical and shear stability
- Excellent rust and corrosion resistance
- Superior oxidation and thermal stability
- Good low temperature performance and pump ability
- Good high temperature performances

Specifications:

- NLGI No. 2



Product Code: 9003

Product Size: 450g, 2.5kg, 20kg, 180kg

V1. 8/23

Product Data Sheet

Lithplex EP2

Typical Characteristics:

Appearance		Smooth, no lumps
Base Oil Viscosity (cSt at 40°C)	ASTM D 7152	220
Colour	Visual	Blue/Green
NGLI Grade	ASTM D 217 mod	2
Drop Point (°C).	IP 396	>250 °C
Emcor Rust Test - Distilled Water	ISO 11007	0
Four Ball EP Test Weld Load	ASTM D 2596	620 kg
FAG FE9 B/6000rpm/1500N/150°C.	DIN 51821	>100h
Penetration 60 Strokes	ISO 2137	265-295
Water Wash Out @ 79°C	ISO 11009	<5%
Temperature Range in °C		-30 to +150 (220 max)
Thickener		Lithium Complex

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website
<http://www.royallubricants.com.au/> or by email: info@royallubricants.com.au