

## Product Data Sheet

### **Nickel Anti-Seize Compound**

*Superior Quality, High Temperature Lubricating Compound*

**Nickel Anti-Seize Compound** is a product that provides lubrication allowing easy assembly and disassembly of metal parts. It provides maximum protection in highly corrosive environments and in the most adverse temperature conditions.

#### **Summary of Benefits:**

- Formulated to provide maximum protection against seizure, galling, rust and corrosion.

#### **Operating Temperature Range:**

Prevents seizure up to 1300°C.

#### **Applications:**

**Nickel Anti-Seize Compound** is recommended for Fittings, Fasteners, Stainless Steel Pipe Fittings, Flanges, and Pump Fittings. Many other applications where a Nickel Based Anti-Seize Lubricant Is Required.



**Product Code:** 9016

**Product Size:** 500g, 20KG

V1 2/07/19

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089 Fax: +61 7 3203 3700**

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441 Fax: +61 3 9768 3325**

## Product Data Sheet

### Nickel Anti-Seize Compound

#### Typical Characteristics:

NLGI	1.5
Appearance	Flecked, silver/grey colour
Penetration @ 25°C	290 min- 320 max
Soap Type	Bentone
Base Oil	Paraffinic, oxidation stable
Dropping Point (°C)	Does not melt
Viscosity @ 40 (°C)	500
Viscosity @ 100 (°C)	32
Solids content % wt	13

\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

#### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

#### Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website [www.royallubricants.com.au](http://www.royallubricants.com.au) or by email: [info@royallubricants.com.au](mailto:info@royallubricants.com.au)

V1 2/07/19

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089 Fax: +61 7 3203 3700**

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441 Fax: +61 3 9768 3325**