



**THE INNOVATIVE  
AUSTRALIAN**

## Product Data Sheet

### Syntec Elite 5W-40

Full Synthetic, Technically Advanced Engine Oil



**Syntec ELITE** is full synthetic, high performance engine oil formulated and blended to achieve the highest levels of engine protection from the latest available technology. As one of the top-tier Low SAPS lubricants, **Syntec ELITE** is specially designed for use in high performance passenger car and light duty vehicles fitted with diesel/petrol engines where advanced after treatment systems such as and Three Way Catalysts (TWC) and Diesel Particulate Filters (DPF) are used.

#### Summary of Benefits:

- Outstanding wear protection at cold start up.
- Higher power output.
- Very low oil consumption due to low volatility.
- Minimises engine emissions, contains lower level of SAPS.

#### Specifications:

- API: SN/CF
- SAE Viscosity: 5W-40
- ACEA: A5/B5-12, C3-16
- Ford: M2C 948-B
- GM: Dexos 2
- GM-LL-B-025
- VW: 502.00, 505.00, 505.01
- Mercedes Benz: MB 229.51, 229.52
- BMW: Long Life 04
- PSA: B71-2290
- Porsche: A40
- Renault: RN0700/RN0710



**Product Code:** 9160

**Product Size:** 1L, 5L, 10L, 20L, 205L, 1000L

V1.1 10/09/2020

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089 Fax: +61 7 3203 3700**

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441 Fax: +61 3 9768 3325**



**THE INNOVATIVE  
AUSTRALIAN**

## Product Data Sheet

### Syntec Elite 5W-40



#### Typical Characteristics:

Density at 15°C (kg/L)	0.888
Flash Point COC (°C)	200
Pour Point (°C)	-42
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	80.8
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	13.9
Sulphated Ash (%m)	0.8
Viscosity Index	179

\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

#### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

#### Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website [www.royallubricants.com.au](http://www.royallubricants.com.au) or by email: [info@royallubricants.com.au](mailto:info@royallubricants.com.au)

V1.1 10/09/2020

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089 Fax: +61 7 3203 3700**

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441 Fax: +61 3 9768 3325**