

## Product Data Sheet

### Ultra 7000 5W-30

Full Synthetic, High Performance Engine Oil



**Ultra 7000 Full Synthetic** is a Long Life, 100% synthetic engine oil that complies with modern European Union emission standards. As one of the top-tier Low SAPS lubricants, it is specially designed for use in high performance passenger car and light duty vehicles fitted with diesel/petrol engines where advanced after treatment systems such as Diesel Particulate Filters (DPF) and Three-Way Catalysts (TWC) are used.

#### Summary of Benefits:

- Maximum engine life
- Reduced emissions
- Maximum power and performance
- Minimum maintenance costs
- Low oil consumption

#### Specifications:

- API: SN/CF
- SAE Viscosity: 5W-30
- ACEA: C3-16, A3/B4-10
- BMW: Longlife 04
- Ford: M2C 948-B
- GM: DEXOS 2 Supersedes GM-LL-A-025, B-025
- Mercedes Benz: MB 229.51, 229.52
- Porsche C30
- PSA: B712290
- VW: 502.00, 505.00, 505.01



**Product Code:** 9240

**Product Size:** 1L, 5L, 10L, 20L, 205L

V1.1 10/09/2020

[WWW.ROYALLUBRICANTS.COM.AU](http://WWW.ROYALLUBRICANTS.COM.AU)

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089** Fax: +61 7 3203 3700

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441** Fax: +61 3 9768 3325

## Product Data Sheet

**Ultra 7000 5W-30**



### Typical Characteristics:

Density at 15°C (kg/L)	0.851
Flash Point COC (°C)	216
Pour Point (°C)	-39
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	64.9
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	10.6
Viscosity Index	168
TBN (mg KOH/g)	7.2

\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website [www.royallubricants.com.au](http://www.royallubricants.com.au) or by email: [info@royallubricants.com.au](mailto:info@royallubricants.com.au)

V1.1 10/09/2020

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089 Fax: +61 7 3203 3700**

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441 Fax: +61 3 9768 3325**