



**THE INNOVATIVE
AUSTRALIAN**

Product Data Sheet

Syntrans MV

Full Synthetic, Multi-Vehicle Automatic Transmission Fluid



PURE SYNTHETIC

Syntrans MV is a multi-vehicle fully synthetic transmission fluid formulated to meet the requirements of most modern and older automatic transmissions. This advanced formulation has passed extensive testing for European, American and Asian vehicles. It offers enhanced transmission shift and anti-shudder performance with high torque capacity.

Suitable for extended drain intervals of up to 150,000 km for general use and 80,000 km for heavy-duty applications. Syntrans MV covers a wide range of specifications making it a true multi-functional product.

Summary of Benefits:

- Outstanding friction and anti-shudder performance
- Excellent viscosity stability in service
- Extra shear strength
- Provides high thermal stability
- Excellent resistance to oxidation
- High fretting resistance
- Cleaner components
- Reduced Oil Inventory

Product Code: 9340

Product Size: 1L, 5L, 20L, 205L

V1. 23/07/2024

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325

Product Data Sheet

Syntrans MV



Specifications:

- Ford M, WSS-M2C924-A, M2C128, M2C195-A, M2C922, FNR5
- GM-IID, IIE, III, IIIF, IIIG, IIH, T-IV, Saturn T-IV, AW-1, TASA
- GM Power Steering Fluid, 9985010, 9985835, DEX, Auto Trak II
- Honda ATF Z-1
- Hyundai/Kia SP, SP-II, SP-III, JWS 3314, JWS 3317, PSF-3
- Idemitsu K17 (JATCO)
- JASO 1-A
- JWS 3309 (Aisin Warner)
- Jatco 3100 PL085 and Jatco Nissan 402
- Kia Red-1, JWS 3314, 3317, KIA SP-II
- Mazda ATF-M III, ATF-M-V
- Mitsubishi PS Fluid, SP-II, SP-III, Diamond SP-III
- Dia Queen ATF J2
- Nissan 402, Nissan Matic-D, J, K
- Nissan Matic C, Nissan SPF-II
- Subaru ATF, ATF-HP and Power Steering Fluid
- Suzuki 3314, 3317
- Toyota T, T-II, T-III, T-IV+
- Toyota PSF Type EH
- BMW 83 22 9 407 807, 83222413477 (ATF 7) 83 22 7 542 290
- Mercedes-Benz; MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9, 236.11, 236.81, 236.91, GL-450
- Mercedes-Benz MB 236.10 (NAG 1 / Shell 3403)
- PSA B71 2340
- Renault DP-0
- Volvo 4speed (P/N 1161521, 1161621)
- Volvo P/N 1161540/1161640
- Volvo 97340, 31256774, 31256776
- VW/Audi G 052 162, G 052 990, G 055 025
- ZF TE-ML 09, 11(3/4/5 speed), ZF Life Guard Fluid 5
- Ford XL-12 Transfer Case
- Allison C-4
- Allison TES-389, TES-389B
- Allison TES-295, TES-668
- MAN 339F, 339 Type L-1, 339 L-2, 339 Type Z-1
- Voith H55.6335
- ZF TE-ML 03D, 04D, 05L, 09, 16L, 17C, 21L
- ZF TE-ML 14A, 11 (3, 4 and 5 speed)
- SAAB 93165147, Power Steer Fluid 2634
- North American High Viscosity ATF
- Aisin Warner JWS 3309
- Porsche 000.043.204.63, 000.043.205.28
- Daihatsu Ammix D III ATF
- Chrysler MS-1872, MS-5931, Mopar 68049954AA
- Mopar AS68/69RC, FCA ATF+2, ATF+3

Note: Not Recommended for Use in Ford Type F/G, DCTs and CVTs

V1. 23/07/2024

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325

Product Data Sheet

Syntrans MV



Typical Characteristics:

Density at 15°C (kg/L)	0.853
Flash Point COC (°C)	224
Pour Point (°C)	-44
Kinematic Viscosity at 40°C mm ² /s (cSt)	33.4
Kinematic Viscosity at 100°C mm ² /s (cSt)	7.1
Viscosity Index	183
Colour	Red

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email: info@royallubricants.com.au.

V1. 23/07/2024

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325