

Syntrans CVT

Full Synthetic, Long Drain Continuously Variable Transmission Fluid



PURE SYNTHETIC

Product Data Sheet

Syntrans CVT fluid is a unique, long drain, Continuously Variable Transmission (CVT) fluid formulated using special synthetic base stocks developed to enhance oxidation stability and thermal resistance, improve low temperature operation and impart specified friction control. Additionally, **Syntrans CVT** has been designed to improve load-carrying ability and resist corrosion and foaming tendency, giving outstanding performance in the Van Doorne push-belt CVT's.

Syntrans CVT is also recommended for Honda CVT's (HMMF) that require a fluid with frictional properties to satisfy Honda's clutch and belt design. Using any other CVT fluid not meeting the same specifications can cause shudder and potential long-term damage to transmission components.

Summary of Benefits:

- Excellent shear stability for consistent shift and protection against wear
- Less deposit formation due to synthetic base stock and outstanding oxidation inhibitors
- Maximises equipment life by maintaining wear protection and oil film thickness

Specifications:

- | | |
|---|---|
| ▪ Audi/VW: G 052 180, G 052 516-A | ▪ Mazda: CVTF 3320 |
| ▪ BMW: EZL 799A Part Nos. 8322 0 136 376/ | ▪ MB: CVT28/236.20 |
| 8322 0 429 154 | ▪ Mini Cooper: EZL 799A, ZF CVT V1 |
| ▪ Chrysler/Jeep: NS-2 | ▪ Mitsubishi: DiaQueen CVTF-J 1, SP-III (CVT) |
| ▪ Daihatsu: Ammix CVTF-DC | ▪ Mopar: CVT +4 |
| ▪ Dodge: CVTF+4/NS-2 | ▪ Nissan: NS-1, NS-2 |
| ▪ Ford: M2C 928-A, CFT30/M2C 933-A | ▪ Saturn: DEX-CVT |
| ▪ Ford: CVT23/Mercon C | ▪ Shell: Green 1V |
| ▪ GM/Saturn: DEX-CVT | ▪ Subaru: e-CVTF, iCVT, Lineartronic CVTF, |
| ▪ Honda: HMMF, HCF-2 | CV-30 |
| ▪ Hyundai/Kia: SP-CVT 1, SP-III (CVT) | ▪ Suzuki: CVTF 3320, TC/ NS-2, CVT Green 1 |
| | ▪ Toyota/Lexus: CVT-TC |
| | ▪ Volvo: 4959 |



Product Code: 9360

Product Size: 1L, 5L, 20L, 205L

V1. 4/07/2019

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325

Product Data Sheet

Syntrans CVT

Full Synthetic, Long Drain Continuously Variable Transmission Fluid



Typical Characteristics:

Density at 15°C (kg/L)	0.856
Flash Point COC (°C)	190
Pour Point (°C)	-47
Kinematic Viscosity at 40°C mm ² /s (cSt)	34
Kinematic Viscosity at 100°C mm ² /s (cSt)	7.1
Viscosity Index	178
Brookfield Viscosity at -40°C mm ² /s (cP)	14,000
Colour	Clear

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email: info@royallubricants.com.au.

V1. 4/07/2019

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325