

Product Data Sheet

Gear Pro 75W-90

High Quality, Easy Shift Manual Gear Oil

GearPro 75W-90 is a high-performance multi-grade manual transmission oil designed for transmissions axles and transaxles, which require an API: GL-5, SAE: 75W-90 lubricant. Ideally suitable for manual gearboxes and differentials offering superior wear protection and excellent low temperature pumpability. It is also Limited Slip Capable

Summary of Benefits:

- Maximises transmission life
- Easy gear selection

Specifications:

■ API: GL-5, MT-1

■ SAE Viscosity: 75W-90

■ MB: 235.5, 235.6

■ SAE: J-2360

■ BTR: 5M-31, 5M-36

■ Ford: M2C 1006-A/B, M2C 1013-A, M2C 104-A, M2C 105-A,

■ GM: HN1181, HN1187, 1386, 1561

■ Mack: GO-H

■ US Military: MIL-L-2105D

■ ZF: TE-ML 02, 05A, 05C, 07A, 08, 12C, 17B

■ Volvo 1273.10

Product Code: 4014

Product Size: 1L, 2.5L, 5L, 20L, 60L 205L

V1.1 6.23



Gear Pro 75W-90

Product Data Sheet

Typical Characteristics:

Density at 15°C (kg/L)	0.88
Flash Point COC (°C)	189
Pour Point (°C)	-33
Kinematic Viscosity at 40°C mm2/s (cSt)	118
Kinematic Viscosity at 100°C mm2/s (cSt)	18
Viscosity Index	171

^{*}Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email info@royallubricants.com.au

40 Kimberley Road, Dandenong South, VICTORIA, AUSTRALIA 3175 **Tel: +61 3 9768 2441** Fax:+61 3 9768 3325