

Product Data Sheet

Gear Pro LS 75W-90

High Quality, Easy Shift Manual Gear Oil

Gear Pro LS 75W-90 is a high-performance multi-grade manual transmission oil designed for transmissions axles and transaxles, which require an API GL-5, SAE Viscosity 75W-90 lubricant. Ideally suitable for manual gearboxes and differentials offering superior wear protection and excellent low temperature pumpability. Suitable for use in both non-Limited Slip and Limited Slip applications.

Summary of Benefits:

- Maximises transmission life
- Easy gear selection

Specifications:

- API: GL-5, MT-1
- SAE Viscosity: 75W-90
- LIMITED SLIP RATED
- SAE: J-2360
- Mack: GO-H
- MAN: 342 M1, M2
- MAN: 342 ML
- MB: 235.5, 235.6
- US Military: MIL-L-2105D
- Volvo: 1273.10
- ZF: TE ML 02, 05, 07, 08

Product Code: 4014

Product Size: 1L, 2.5L, 5L, 20L, 60L 205L, 1000L



11.3.19 V1

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325



**THE INNOVATIVE
AUSTRALIAN**

Gear Pro LS 75W-90

Product Data Sheet

Typical Characteristics:

Density at 15°C (kg/L)	0.88
Flash Point COC (°C)	189
Pour Point (°C)	-33
Kinematic Viscosity at 40°C mm ² /s (cSt)	118
Kinematic Viscosity at 100°C mm ² /s (cSt)	18
Viscosity Index	171

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email info@royallubricants.com.au

11.3.19 V1

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325