



# **Product Data Sheet**

### **Syntec Zero 40** High Performance, Full Synthetic Engine Oil

PURE SYNTHETIC

*Syntec Zero 40* 100% fully synthetic motor oil that complies with modern European and North American emission standards. As one of the top-tier lubricants, it is specially designed for use in high performance passenger cars.

*Syntec Zero 40* aligns well with many OEM performance specifications and can be used in many advanced European, American and Japanese model vehicles.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Summary of Benefits:

- Maximum engine life
- Easy start-up with reduced wear
- Reduced emissions
- Maximum power and performance
- Minimum maintenance costs
- Low oil consumption

### Specifications:

- API: SN/CF
- SAE Viscosity: 0W-40
- ACEA: A3/B4-08
- ILSAC: GF-5

### Product Code: 9185

**Product Size:** 1L, 5L, 20L, 205L



#### V1.1 10/09/2020

WWW.ROYALLUBRICANTS.COM.AU Brisbane: 1-7 Potassium Street, Narangba, QUEENSLAND, AUSTRALIA 4504 Tel: +61 7 3203 0089 Fax:+61 7 3203 3700

*Melbourne:* 40 Kimberley Road, Dandenong South, VICTORIA, AUSTRALIA 3175 **Tel: +61 3 9768 2441** Fax:+61 3 9768 3325

... DRIVEN BY PERFECTION





## **Product Data Sheet**

### Syntec Zero 40

PURE SYNTHETIC

### Typical Characteristics:

Density at 15°C (kg/L)	0.841
Flash Point COC (°C)	230
Pour Point (°C)	-35
Kinematic Viscosity at 40°C mm2/s (cSt)	83.2
Kinematic Viscosity at 100°C mm2/s (cSt)	14.09
TBN (mg KOH/g)	7.7
Viscosity Index	175
Sulphated Ash (%m)	0.94
HTHS Viscosity (mPa.s)	3.85
CCS @ -35 °C (cP)	4036

\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

*The Safety Data Sheet is available at Royal Precision Lubricants website <u>www.royallubricants.com.au</u> <i>or by email: <u>info@royallubricants.com.au</u>* 

V1.1 10/09/2020

WWW.ROYALLUBRICANTS.COM.AU Brisbane: 1-7 Potassium Street, Narangba, QUEENSLAND, AUSTRALIA 4504 Tel: +61 7 3203 0089 Fax:+61 7 3203 3700 ...DRIVEN BY PERFECTION Melbourne: 40 Kimberley Road, Dandenong South, VICTORIA, AUSTRALIA 3175 Tel: +61 3 9768 2441 Fax:+61 3 9768 3325