

Syntec Ultra F 5W-30

Full Synthetic, Extreme Fuel-Efficient Motor Oil

Product Data Sheet



Syntec Ultra F 5W-30 is a full synthetic fuel-efficient passenger car motor oil formulated for Ford passenger car engines. Especially suitable for Ford Dura Torque Diesel engines.

Syntec Ultra F 5W-30 meets the latest Ford and ACEA performance levels and exceeds the most demanding requirements in relation to modern engine's emission controls as well as oil consumption. **Syntec Ultra F 5W-30** is suitable for use in approved European and US passenger cars and 4WD's.

Summary of Benefits:

- Wear protection and extended service life
- Outstanding low temperature viscometrics for reduced wear at start up
- Piston cleanliness and engine sludge protection
- Emission system durability and excellent fuel economy

Specifications:

- SAE Viscosity 5W-30, API: SN/CF
- ACEA A1/1, A5/B5-16
- Opel GM-LL-B-025
- Chrysler MS 6395
- Iveco 18-1811 S1/S2
- Ford M2C 913-A, B, C, D
- Renault RN0700, 0710
- VW 502.00, 505.00
- Jaguar M2C 913-B
- Jaguar Land Rover ST JLR.03.5003
- Mercedes 229.1, 229.3

Product Code: 9187

Product Size: 1L, 5L, 10L, 20L, 60L, 205L



V1.2 6.23

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325

Product Data Sheet

Syntec Ultra F 5W-30

Typical Characteristics:

Density at 15°C (kg/L)	0.85
Flash Point COC (°C)	228
Pour Point (°C)	-34
Kinematic Viscosity at 40°C mm ² /s (cSt)	60.2
Kinematic Viscosity at 100°C mm ² /s (cSt)	10.3
Viscosity Index	160
CCS (-30°C)	3990
TBN, ASTM D2896 (mg KOH/g)	9.5
Sulphated Ash (%)	1.2

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants www.royallubricants.com.au or by email: info@royallubricants.com.au

V1.2 6.23

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325