

Nexus 4T Super 20W-50

High Performance, 4 Stroke Motorcycle Engine Oil



Nexus 4T Super 20W-50 is a premium, 4 stroke motorcycle engine oil formulated and blended to achieve the highest levels of engine and gearbox protection from the latest available technology.

Scientifically formulated, the combination of ultra-shear stable base oils, Titanium additive and ZDDP (Zinc) levels work together synergistically to ensure Nexus 4T Super 20W-50 delivers exceptional performance providing outstanding wear protection, low temperature and high temperature performance

Applications:

Nexus 4T Super 20W-50 is suitable for use in all 4 stroke engines air-cooled or liquid-cooled requiring an oil meeting the API SG/SH/SJ/SL/SM/SN standards and can be used where semi-synthetic or other types of 20W-50 oils are specified by the manufacturer.

Nexus 4T Super 20W-50 is designed for use in most modern four stroke road & sports bikes, dirt & enduro bikes, ATVs/Quad bikes and 4 stroke scooter with or without integrated gearboxes and wet or dry clutches.

Nexus 4T Super 20W-50 is non friction modified for maximum wet clutch performance.



V1.2 12/2016

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia, 4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



Summary of Benefits

- A combination of Titanium and ZDDP (Zinc) protects against component wear.
- Titanium Technology maximizes bearing protection and offers superior anti-wear protection.
- Quality anti-wear chemistry reduces bearing and valve train wear and prevents scuffing.
- Smooth power transfer prevents clutch grabbing for an easily controlled and efficient gear shifting and clutch operation.
- Superior deposit control cleans and minimises engine sludge.

Specifications:

- API: SN
- SAE Viscosity: 20W-50
- JASO MA2 (T903:2011)

Product Code: 1722

Product Size: 1L, 4L, 20L, 205L

Typical Characteristics:

Density at 15°C (kg/L)	0.87
Flash Point COC (°C)	220
Pour Point (°C)	-30
Kinematic Viscosity at 40°C mm ² /s (cSt)	138.0
Kinematic Viscosity at 100°C mm ² /s (cSt)	16.9
Viscosity Index	133
Sulphated Ash (%m)	0.78

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

V1.2 12/2016

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700





Product Data Sheet

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au

V1.2 12/2016

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

