

## C4 Hydraulic 10W

### High Performance Hydraulic Fluid

C4 Hydraulic 10W is a high performance hydraulic oil formulated from advanced base oils and a balanced additive system designed to satisfy a wide range of heavy-duty hydraulic equipment requirements. This product is specifically engineered using an effective balance of ash-less dispersants and metallic detergents combined with inhibitors to control oxidation, wear, corrosion and rust.

C4 Hydraulic 10W is used in a wide range of on and off-highway hydraulic oil designed to satisfy a wide range of heavy-duty hydraulic equipment requirements both on and off-highway.

#### Summary of Benefits

- Clean hydraulic systems
- Less wear especially in vanes and control valves
- Protects against vane sticking
- Extends drain intervals with oil analysis
- Good anti-wear protection
- Reduces premature wear and extends equipment life
- Wide temperature range performance
- Reduces wear at cold start-up temperatures
- Effective lubrication film strength at high temperatures
- Protects against rust and corrosion
- Long equipment life and lower maintenance costs

#### Specifications:

- SAE Viscosity: 10W
- MIL-L-2104 D & E
- Allison: C-4
- Caterpillar: TO-2
- ZF TE-ML 02C

V1.1 10/17

Victoria  
40 Kimberly Road, Dandenong South, Victoria Australia 3175  
PO Box 4580, Dandenong South, Victoria Australia 3164  
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland  
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504  
PO Box 139, Deception Bay, Queensland, Australia, 4508  
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



## C4 Hydraulic 10W

Product Code: 3700

Product Size: 20L, 205L

### Typical Characteristics:

Density at 15°C (kg/L)	0.88
Flash Point COC (°C)	226
Pour Point (°C)	-33
Kinematic Viscosity at 40°C (cSt)	44.3
Kinematic Viscosity at 100°C (cSt)	6.8
Viscosity Index	108
Total Base Number (mgKOH/g)	7.5
Sulphated Ash (%m)	1.0

\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:  
[info@royallubricants.com.au](mailto:info@royallubricants.com.au).

V1.1 10/17

Victoria  
40 Kimberly Road, Dandenong South, Victoria Australia 3175  
PO Box 4580, Dandenong South, Victoria Australia 3164  
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland  
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504  
PO Box 139, Deception Bay, Queensland, Australia, 4508  
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

