

Syngear LS 75W-90

Full Synthetic, Limited Slip Gear Oil



Syngear LS is a multi-grade lubricant containing a selected blend of synthetic base and extreme pressure additives, and is designed to give maximum protection to gearboxes and differentials under the most arduous operating conditions where heat and load are major factors.

Summary of Benefits

- Reduces maintenance costs
- Maximises equipment life
- Wide temperature application
- Extends drain periods
- Smooth limited slip operation

Specifications:

- API: GL-5, MT-1
- SAE Viscosity: 75W-90, J2360
- Military: MIL-PRF-2105 E, MIL-L-2105 D
- General Motors: HN-1561, HN-2040
- Ford: M2C 118-A, M2C 104
- Mack: GO-J
- Borg Warner: 5M-48
- Arvin Meritor: 0-76E, 0-76N, (Synth.75W-90)

Product Code: 9410

Product Size: 2.5L, 5L, 205L



V1.1 10/17

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



Syngear LS 75W-90



Typical Characteristics:

| | |
|---|--------|
| Density at 15°C (kg/L) | 0.85 |
| Flash Point COC (°C) | 207 |
| Pour Point (°C) | -45 |
| Kinematic Viscosity at 40°C mm ² /s (cSt) | 108.9 |
| Kinematic Viscosity at 100°C mm ² /s (cSt) | 17.5 |
| Viscosity Index | 178 |
| Brookfield Viscosity at -40°C mm ² /s (cP) | 85,000 |

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.

V1.1 10/17

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

