

Hydrol Retain HE 46 & 68

High Efficiency Multi Grade Hydraulic Fluid

Hydrol Retain HE products are specifically designed to keep their viscosity over a much broader temperature range. This means the fluid that can meet the low temperature requirements and still retains sufficient viscosity to protect and reduce leakage at high temperatures. This significantly improves pump and motor efficiency. Hydrol Retain HE gains its Multi Grade characteristics from a cutting edge shear stable high efficiency polymer. Unlike cheaper polymers designed for shorter oil drain intervals in engine oil, this additive ensure Hydrol Retain HE maintains its viscosity (multi grade) throughout its working life.

The improved efficiencies at start-up and hot running can provide fuel savings of 5-30% in mobile plant.

Summary of Benefits

- Wide operating temperature range (at least 15 °C more than a mono grade)
- Reduced power during start-up.
- Reduced internal leakage improving efficiency and running cooler.
- Superior fine filterability even in wet conditions.
- Leading performance in anti-wear protection, oxidation resistance and thermal stability.
- Top in class shear stability ensures constant oil viscosity throughout the oil drain interval.
- Long fluid life due to enhanced chemical and thermal stability.

Specifications:

Cincinnati Milacron, P-68, P-69, P-70
Denison HF0, HF1, HF2
DIN 51524 Part 2 (HLP) & Part 3 (HVLP)
Eaton Brochure 694 for VQ25A (formerly M-250-S and I-286-S)
Ford M6C 32
GM LS2
ISO 11158 Categories HM and HV
ASTM D 6158 Type HM and HV
AFNOR NF E48-603

V1.0 10/17

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



Hydrol Retain HE 46 & 68

Product Code: 5303 Hydrol Retain HE 46

Product Code: 5304 Hydrol Retain HE 68

Product Size: 20L, 205L, 1000L

Typical Characteristics:

	46	68
Density at 15°C (kg/L)	0.85	0.87
Kinematic Viscosity at 40°C mm ² /s (cSt)	46.9	67.8
Kinematic Viscosity at 100°C mm ² /s (cSt)	8.9	11.4
Viscosity Index	173	163
Flash Point COC (°C)	216	226
Pour Point (°C)	-47	-45

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email.

V1.0 10/17

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia, 4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

