

Ultra Mono Diesel Oils

High Performance Engine Oil for Superior Wear and Protection

Ultra Mono is a range of high performance mid-ash, mixed fleet mono grade engine oils designed for a wide range of diesel and petrol engines. Recommended for a wide range of European, Japanese and pre-1994 American makes of diesel engines.

Ultra Mono can be used in non-engine applications such as off-highway, agricultural and stationary plant operations, where appropriate.

Summary of Benefits

- Designed for a wide range of older engines including Cummins, Caterpillar, Mack, MAN, MB and Hino.
- Provides excellent protection against corrosion and wear throughout the recommended oil drain period.
- Excellent shear and oxidation stability ensure adequate oil life.

Specifications:

<ul style="list-style-type: none"> ▪ API: CF/SJ ▪ SAE Viscosity: 10W, 30, 40, 50 ▪ ACEA: E2 (SAE 30, 40) ▪ Allison C-4 ▪ Caterpillar: ECF-2, ECF-1-a ▪ Detroit Diesel: DDC Category 1 (SAE 30, 40) ▪ Japan: Japanese CD 	<ul style="list-style-type: none"> ▪ JASO: DH-1 ▪ Mack: EO-K/2 ▪ MAN: 270 ▪ MB: 228.0 (SAE 30, 40) ▪ MIL-L-2104 F (SAE 30, 40) ▪ MIL-L-46152 D (SAE 10W, 30) ▪ MTU: Category 1 (SAE 30, 40) ▪ ZF: TE-ML 03B (SAE 10W)
--	---

Product Code: 10W 2210, 30 2230, 40 2240, 50 2250

Product Size: 20L, 60L, 205L, 1000L

V1.1 10/2017

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia, 4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



Ultra Mono Diesel Oils

Typical Characteristics:

	10W	30	40	50
Density @15°C	0.897	0.901	0.902	0.904
Flash Point °C COC	210	225	230	235
Pour Point °C	-33	-21	-18	-12
Kinematic Viscosity at 40°C cSt	41.5	102	142	200
Kinematic Viscosity at 100°C cSt	6.3	11.5	14.4	18.5
Viscosity Index	98	99	99	102
Total Base Number (mgKOH/g)	7.4	7.4	7.4	7.4
Sulphated Ash (%m)	1.05	1.05	1.05	1.05

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.

V1.1 10/2017

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

