

Nickel Anti-Seize Compound

Superior Quality, High Temperature Lubricating Compound

Nickel Anti-Seize Compound is a product that provides lubrication allowing easy assembly and disassembly of metal parts. It provides maximum protection in highly corrosive environments and in the most adverse temperature conditions.

Summary of Benefits

- Formulated to provide maximum protection against seizure, galling, rust and corrosion.

Operating Temperature Range:

Prevents seizure up to 1300°C.

Applications:

Nickel Anti-Seize Compound is recommended for Fittings, Fasteners, Stainless Steel Pipe Fittings, Flanges, and Pump Fittings. Many other applications where a Nickel Based Anti-Seize Lubricant Is Required.



Product Code: 9016

Product Size: 500g

V1.1 07/18

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia, 4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



Nickel Anti-Seize Compound

Typical Characteristics:

NLGI	1.5
Appearance	Flecked, silver/grey colour
Penetration @ 25°C	290 min- 320 max
Soap Type	Bentone
Base Oil	Paraffinic, oxidation stable
Dropping Point (°C)	Does not melt
Viscosity @ 40 (°C)	500
Viscosity @ 100 (°C)	32
Solids content % wt	13

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

V1.1 07/18

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

