



**THE INNOVATIVE
AUSTRALIAN**

Syntec

Marine 4 Stroke 10W-40

High Performance, Synthetic Engine Oil for 4 Stroke Engines

Syntec Marine 4 Stroke 10W-40 is a premium, full synthetic 4-stroke engine oil for outboard engines, personal water craft, all-terrain vehicles and snowmobiles. Formulated to provide enhanced corrosion and oxidation protection for modern engines operating in marine and salt water environments. Its advance additive technology protects your engine during off season lay down periods by providing superior rust and oxidation resistance.

Developed to meet the latest engine cleanliness and wear protection tests Syntec Marine 4 Stroke also complies with the latest NMMA FC-W Catalyst Compatible™ specifications.

Summary of Benefits:

- Reduces engine corrosion due to water in oil
- Provides superb engine cleanliness
- Hyper ZDP enhances wear protection whilst preserving catalyst life
- Suitable for engines with superchargers

Specifications:

- NMMA FC-W
- NMMA FC-W Catalyst Compatible™
- SAE Viscosity: 10W-40
- JASO: MA (T903:2011)
- API: SM

Product Code: 1840

Product Size: 1L, 4L, 20L, 205L, 1000L



V1 3/12/19

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325



**THE INNOVATIVE
AUSTRALIAN**

Syntec

Marine 4 Stroke 10W-40

High Performance, Synthetic Engine Oil for 4 Stroke Engines

Typical Characteristics:

Density at 15°C (kg/L)	0.8
Flash Point COC (°C)	210
Pour Point (°C)	-24
Kinematic Viscosity at 40°C mm ² /s (cSt)	89
Kinematic Viscosity at 100°C mm ² /s (cSt)	13.
Viscosity Index	153

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website:

www.royallubricants.com.au or by email: info@royallubricants.com.au

V1 3/12/19

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325