

Product Data Sheet

Power Steer Fluid

Premium Mineral, High Performance

Power Steer Fluid is a premium mineral steering fluid suitable for use in a wide range of power steering systems. It contains a seal swell additive to reduce leaks and an anti-shudder additive not found in Automatic Transmission Fluids (ATFs). It can be used to top up select power steering fluids and systems.

It **cannot be used in Honda or Acura** power steering systems or **Ford** AU, BA, BF, **FPV** or **Tickford** systems, or where **Vegetable Oils** or **Brake Fluid** is specified.

Summary of Benefits:

- It can be used to top up or replace mineral power steering fluids (ATF Dexron type fluids).
- Controls seal swelling and protects pump parts against wear while providing the proper friction coefficient for proper system operation.
- Contains a unique seal conditioning agent and foam inhibitor benefiting vehicles operating under the most severe conditions.
- It can be used for complete replacement where the below specifications are called for:



Specifications:

Meets or exceeds the following international performance specifications:

- | | |
|---------------------------------------|-------------------------------------|
| • Hyundai: PSF-3 | • Nissan: PSF-II |
| • Kia: PSF-3 | • GM: P/N 89021184 |
| • Mercedes Benz: 236.3 | • GM: 9985010, P/N 1052884 |
| • Chrysler: MS-5931 | • Saab: P/N K0209A0080 |
| • Mitsubishi PS Fluid, Diamond SP III | • Subaru P/N (45) 30 90 800 |
| • Ford: M2C195-A | • Toyota: PSF Type EH, P/N 08886-01 |

*For the very latest specification listing please refer to this products Data Sheet at www.royallubricants.com.au

V1.0 03/20

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325



**THE INNOVATIVE
AUSTRALIAN**

Product Data Sheet

Power Steering Fluid

Product Code: 3152

Product Size: 1L, 20L

Typical Characteristics:

Flash Point	210
Kinematic Viscosity at 40°C mm ² /s (cSt)	43
Kinematic Viscosity at 100°C mm ² /s (cSt)	7.1
Viscosity Index ASTM D2270	126
Colour	Green

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email: info@royallubricants.com.au

V1.0 03/20

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325