

## Product Data Sheet

### All- Fleet SFX

10W-40 Synthetic Fortified Multi-Fleet Engine Oil

**All-Fleet SFX** is a Synthetic Fortified, premium performance engine oil, developed to provide superior performance and wear protection under the operating conditions likely to be experienced in modern petrol or diesel passenger vehicles, turbocharged, carburettor, or fuel injected models.

#### Summary of Benefits:

- It incorporates the latest Synthetically Fortified base oil technology and includes the most advanced dispersant and detergent technology available to keep the engine clean and free of sludge.
- This oil offers superior wear protection under high stress conditions.
- The multi-grade properties provide rapid circulation to help overcome wear associated with cold starts, smoother idling and greater engine efficiency.

#### Specifications:

- API: SQ/CF
- SAE Viscosity: 10W-40
- Chrysler: MS 6395
- Ford: M2C 945-A, 946-A
- GM: 6094M
- Mercedes: 229.1
- VW: 501.01, 505.00
- 



**Product Code:** 1055

**Product Size:** 20L, 205L, 1000L



V1.0 09/20

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089 Fax: +61 7 3203 3700**

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441 Fax: +61 3 9768 3325**

## Product Data Sheet

### All- Fleet SFX

10W-40 Synthetic Fortified Multi-Fleet Engine Oil

#### Typical Characteristics:

Specific Density at 15°C (kg/L)	0.873
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	123
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	15.0
Ash (%)	<1.0
Viscosity Index	125
Sulphated Ash (%m)	<1.0
Phosphorus Mass (%m)	0.09
Base Number (mg KOH/g)	8.57

*\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability*

#### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

#### Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website [www.royallubricants.com.au](http://www.royallubricants.com.au) or by email: [info@royallubricants.com.au](mailto:info@royallubricants.com.au)

V1.0 09/20

**WWW.ROYALLUBRICANTS.COM.AU**

**Brisbane:**

1-7 Potassium Street, Narangba,  
QUEENSLAND, AUSTRALIA 4504

**Tel: +61 7 3203 0089 Fax: +61 7 3203 3700**

**...DRIVEN BY PERFECTION**

**Melbourne:**

40 Kimberley Road, Dandenong South,  
VICTORIA, AUSTRALIA 3175

**Tel: +61 3 9768 2441 Fax: +61 3 9768 3325**