



**THE INNOVATIVE
AUSTRALIAN**

Product Data Sheet

All Fleet 15W-40

High Performance Synthetic Fortified Engine Oil

All Fleet 15W-40 is a multi-functional petrol/diesel oil suitable for older generation motors, it provides excellent protection from piston deposits, less oil thickening and sludge deposits, and exceptional anti-wear protection under high speed, high stress motoring conditions.

ALL Fleet 15W-40 has a high viscosity index, ensuring quick circulation of oil to all moving parts during cold weather starts, providing additional wear protection during this critical time of an engine's operation.

Summary of Benefits:

- It incorporates the latest mineral oil technology that includes the most advanced dispersant and detergent technology available to keep the engine clean and free of sludge.
- This oil offers superior wear protection under high stress conditions.
- The multi-grade properties provide rapid circulation to help overcome wear associated with cold starts, smoother idling and greater engine efficiency.

Specifications:

- API: SQ/CF
- SAE Viscosity: 15W-40
- ACEA: A2/B2-02
- Ford: M2C 153-E
- Mercedes Benz: 229.1
- MIL-L-46152 E, 2104 E
- VW: 500.00, 501.00



Product Code: 2005 (formerly 2000P)

Product Size: 20L, 205L, 1000L

14.02.19 V1

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325



**THE INNOVATIVE
AUSTRALIAN**

Product Data Sheet

All Fleet 15W-40

Typical Characteristics:

Density at 15°C (kg/L)	0.8
Kinematic Viscosity at 40°C mm ² /s (cSt)	120
Kinematic Viscosity at 100°C mm ² /s (cSt)	15.
Viscosity Index	138
Sulphated Ash (%m)	<1.
Total Base Number (mg KOH/g)	7.2

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email info@royallubricants.com.au

14.02.19 V1

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325