



**THE INNOVATIVE
AUSTRALIAN**

MULTI GRADE

Four Stroke 10W-30

Premium, Lawn Mower and Stationary Engine Motor Oil

Four Stroke 10W-30 Lawn Mower and Stationary Engine Oil is a multigrade SAE Viscosity 10W-30 crankcase oil designed for small petrol and light diesel engines. It controls oil consumption and deposits and protects against rust, corrosion and wear, leading to longer engine life. Recommended for four stroke petrol lawn mower engines running on leaded, unleaded or lead replacement petrol. Especially suitable for Honda, Husqvarna, Kawasaki, Toro, Yamaha and many other small four stroke petrol and diesel stationary engines. It is not recommended for two stroke petrol or two stroke diesel engines.

Summary of Benefits:

- Meet warranty service requirements for a wide range of modern diesel and petrol engines.
- Maximise engine life by controlling deposits and protecting against wear of highly loaded components under severe service conditions.
- Reduce maintenance costs by maximising oil filter life and engine overhaul periods.
- Maintain excellent control of oil consumption.
- Protect against rust and corrosion.

Specifications:

- API: SL/CF
- SAE Viscosity: 10W-30
- ACEA: A3 / B3
- Japan: Japanese CF

Product Code: 1831

Product Size: 1L, 5L, 20L, 205L



14.10.21 V1

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325



**THE INNOVATIVE
AUSTRALIAN**

MULTI GRADE

Four Stroke 10W-30

Premium, Lawn Mower and Stationary Engine Motor Oil

Typical Characteristics:

Density at 15°C (kg/L)	0.871
Flash Point COC (°C)	200
Pour Point (°C)	-30
Kinematic Viscosity at 40°C mm ² /s (cSt)	80
Kinematic Viscosity at 100°C mm ² /s (cSt)	11.5
Viscosity Index	135
Sulphated Ash (%m)	<1.0
Total Base Number (mg KOH/g)	5.9

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Safety Data Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email info@royallubricants.com.au

14.10.21 V1

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325