

Product Data Sheet

Syntec Euro C5

Full Synthetic Passenger Car Engine Oil



Syntec Euro C5 is a high performance, fully synthetic, low viscosity engine oil suitable for use in diesel and petrol fuelled vehicles that call for an ACEA C5 rated 0W-20 oil, such as some recent Toyota and Hyundai.

Formulated using the latest cutting-edge additive technology, **Syntec Euro C5** maximises fuel economy while at the same time extends Diesel Particulate Filter Life (DPF) and drain intervals.

Summary of Benefits:

- Longer drain intervals
- Better fuel economy from low viscosity
- Enhanced LSPI Protection
- Preserved performance of DPF and TWC filter systems

Specifications:

- API: SP and RC SAE: 0W-20
- ACEA: C5-21, C6-21
- ILSAC: GF-6A
- BMW: LL17FE+, LL14FE+
- Chrysler: MS-12145
- Fiat: 9.55535-GSX
- Ford: M2C 947-B1, M2C 962-A1
- JLR: STJLR 03-50006-16
- Mercedes: 229.71, 229.72
- Opel: OV 040 1547
- Renault: RN17FE
- Volvo: VCC RBS)-2AE

Product Code: 9110

Product Size: 6L, 10L, 20L, 205L



V1.1 20/07/2022

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325

Product Data Sheet

Syntec Euro C5 0W-20



Typical Characteristics:

Density at 15°C (kg/L)	0.85
Flash Point COC (°C)	228
Pour Point (°C)	-39
Kinematic Viscosity at 40°C mm ² /s (cSt)	48.0
Kinematic Viscosity at 100°C mm ² /s (cSt)	8.7
Viscosity Index	162
TBN (mg KOH/g)	8.3
Sulphated Ash (%)	0.81

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product. A Sheet is available at Royal Precision Lubricants website www.royallubricants.com.au or by email: info@royallubricants.com.au

V1.1 20/07/2022

WWW.ROYALLUBRICANTS.COM.AU

Brisbane:

1-7 Potassium Street, Narangba,
QUEENSLAND, AUSTRALIA 4504

Tel: +61 7 3203 0089 Fax: +61 7 3203 3700

...DRIVEN BY PERFECTION

Melbourne:

40 Kimberley Road, Dandenong South,
VICTORIA, AUSTRALIA 3175

Tel: +61 3 9768 2441 Fax: +61 3 9768 3325