

Product Data Sheet

SYNGEAR ECO DRIVE

Limited Slip, Extreme Pressure Gear Oil



Syngear ECO DRIVE is a 75W-85, full synthetic, thermally stable, extreme pressure gear oil. It is formulated with top tier extreme pressure additives supplemented with anti-wear additives to provide maximum protection. It also contains limited slip protection and is an excellent fuel-efficient gear oil.

Syngear ECO DRIVE is engineered to provide high performance in differentials, axles and some transaxles requiring a low viscosity GL-5 oil. Syngear Eco Drive is suitable for many late model vehicles.

Summary of Benefits

- Good thermal stability and resistance to oxidation extends drain intervals
- Formulated to provides extended component life
- Improved fuel efficiency
- Reduce wear and maintenance costs
- Excellent protection against deposits and sludge for extended drive train life

Specifications:

- | | |
|-------------------------|---------------------------------|
| ▪ API: GL-5 | ▪ Ford: M2C 83-C |
| ▪ SAE Viscosity: 75W-85 | ▪ Mitsubishi: ES-X-64021 |
| ▪ SAE: J-2360 | ▪ VW: TL 521 45-X (G052 145 A1) |
| ▪ BTR: 5M-42 | ▪ ZF: TE-ML 18 |

Product Code: 9395

Product Size: 4L, 20L, 205L



V1.0 6/23

Brisbane:
1 Potassium Street, Narangba
Queensland, AUSTRALIA 4504
Tel: +61 7 3203 0089

Melbourne:
40 Kimberly Road, Dandenong South
Victoria, AUSTRALIA 3175
Tel: +61 3 9768 2441

Townsville:
13 Elquestro Way, Bohle, Townsville
Queensland, AUSTRALIA 4818
Tel: +61 7 3203 0089

Perth:
A 11/550 Canning Hwy, Attadale
Western Australia, AUSTRALIA 6156
Tel: +61 8 6461 6868

...DRIVEN BY PERFECTION

royallubricants.com.au



**THE INNOVATIVE
AUSTRALIAN**

Product Data Sheet

SYNGEAR

ECO DRIVE

Limited Slip, Extreme Pressure Gear Oil

Typical Characteristics:

Viscosity @ 40°C cSt	79.0
Viscosity @ 100°C cSt	12.3
Viscosity Index	153
Density @ 15°C (kg/L)	0.86
Flash Point COC (°C)	>210
Pour Point (°C)	-42

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment:

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

*The Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.*

V1.0 6/23

Brisbane:
1 Potassium Street, Narangba
Queensland, AUSTRALIA 4504
Tel: +61 7 3203 0089

Melbourne:
40 Kimberly Road, Dandenong South
Victoria, AUSTRALIA 3175
Tel: +61 3 9768 2441

Townsville:
13 Elquestro Way, Bohle, Townsville
Queensland, AUSTRALIA 4818
Tel: +61 7 3203 0089

Perth:
A 11/550 Canning Hwy, Attadale
Western Australia, AUSTRALIA 6156
Tel: +61 8 6461 6868

...DRIVEN BY PERFECTION

royallubricants.com.au